

Films

Toner

Water

(eco) Solvent

UV Curable

UVgel

Latex

IJM366 PVC Display Film, Matte 220 µm

Product Description White, high-opacity, rigid PVC film with a matte, microporous coating for indoor roll-up displays and display stands

Physical Properties	Thickness	220 µm	ISO 534
	Weight	295 g/m ²	ISO 536
	Opacity	98 %	ISO 2471

Applications/features

- Roll-up displays
- Display stands
- Exhibition panels
- Indoor signage
- Posters
- Instant-dry, microporous coating
- Brilliant colour reproduction
- Non-reflective matt surface
- Suitable for dye and pigment inks
- Highly opaque, scratch resistant

Available Widths (mm)	3"core	594	841	914	1067														
	Refer for our current offering to www.canon-europe.com/mediaguide																		

Storage Conditions Shelf life: 1 year, Temperature 15-30°C, Relative Humidity 30-70%
Repack opened rolls when not in use.

Print Conditions Best results are obtained at 20°C and 65% RH.

Environment, Health & Safety No Material Safety Data Sheet required. No special hazards anticipated under normal conditions encountered in storage, processing and disposal. Waste disposal methods: incineration or landfill.

Lamination Compatibility	Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
	yes	no	no	

Outdoor Use This film is not suitable for outdoor use.

Colour Profiles Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Processing Guidelines

Printing guidelines

Side to be printed is the outer side of the roll. By nature the film induces a static charge when (un)winding, therefore precautions should be made to prevent this from influencing the print.

Use of gloves is recommended.

Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects.

Print results will vary for different printer/ink combinations.

Canon media profiles include recommended ink/toner

restrictions and printer parameters. Depending on environment and application, printer parameters may have to be adjusted slightly in order to obtain the best results.

For UVgel technology, only compatible in matte print modes.

Application guidelines

It is necessary to protect the surface if it is subject over a long time to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate.

We recommend to use self-adhesive laminating foils for cold lamination.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition 0715

© Canon Europa N.V., 2024

