



Models may vary from the image shown

This innovative AK-C7412 Medical Keyboard combines a full number pad and an integrated touchpad, offering unparalleled versatility in any clinical or industrial setting. Its sleek, ergonomic design and the integrated scissor technology ensure a perfect typing feel, allowing for smooth and responsive input, even during long shifts. But what truly sets this keyboard apart is its exceptional disinfection capabilities due to the flat key profile. The durable silicone cover can withstand rigorous cleaning protocols, ensuring a safe and hygienic workspace. With the touchpad, you can easily navigate without the need for an external mouse, maximizing your efficiency and minimizing clutter.

FUNCTION AND PERFORMANCE

- ightarrow Hygiene Keyboard for Clinical Wipe Disinfection
- → Available as a wired variant and a rechargeable wireless variant
- → Clinical Wipe Disinfection with all common Disinfectants according to German Guidelines VAH/DGHM
- → Utmost Writing Comfort by Scissors Balancing Technology
- \rightarrow Perfect writing in Hygiene Critical Applications

- → Fully Sealed Key Membrane for Protection Class IP68
- → CleanFunction allows to switch off Keys during Cleaning Process
- ightarrow 4 Threaded Holes for VESA Mounting
- ightarrow German Brand Product

TECHNICAL DATA

-		
Color:	white	
Weight main product:	604 g	
Weight of product without packaging:	600 g	
Weight of product incl. packaging:	720 g	
Weight of master carton incl. content:	13,300 g	
Content of master carton (pieces):	20	
Dimensions product without packaging:	365 mm x 139 mm x 17 mm	
Dimensions product incl. packaging:	380 mm x 205 mm x 25 mm	
Dimensions master carton:	400 mm x 273 mm x 447 mm	
Cable length:	180 cm	
Storage temperature:	-20 °C - 60 °C	
Working temperature:	0 °C - 50 °C	
Product approvals:	 CE EU RoHS FCC EN60601-1-2-2015 (IEC 4th edition) 	
System	USB-A	
Requirements- Hardware:		
Operating system:	All operating systems that support USB keyboard interface	
Scope of delivery:	KeyboardManual	
Reliability:	MTBF 90: > 10 Mio.	
Switching characteristics:	tactile	



Max. current consumption (mA) of keyboard:	32 mA	Reprocessing:	Recommended for Wipe DisinfectionApproved for wipe
Actuating force (cN):	60 cN		disinfection according to
Total Key Travel:	2,5 mm		CDC Guideline for
Key labeling:	Silk screen printing on silicon membrane		Disinfection and Sterilization in
Number of keys:	105		Healthcare Facilities with
Special key functions:	FN KeyCleanFunction		EPA-registered disinfecting products • Chemical-Thermal
Status LEDs:	in housing	 Disinfection with IP68 Sealing Caps Mounted Water Tight (IP68) 	
Key technology:	Scissor		
Keycap material:	ABS		
		EAN:	7061119200609
		Protection class:	IP 68

Warranty: 2 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.