

Esc			*1		F2		F3		14		2	8	18		17		F8			F9		F10	1	r1 F12	Druck S-Adr	Rolen	Passe Unity	2	in Cape	Scroll c	lean .
	1		2		9 3	•	\$ 4		% 5		8 6	17	ę	(8	1	) 9	1	=	}	? B			•	- Backspace	Entp	Pps1	Bid!	Num (j)	+	×	-
τιο <del>Η</del>		Q	•	W		E	e	R		т		z	U		1		0		Ρ		Û		* +~	Enter and	Ent	Ende	and 4	7 Post	8 †	9 Did1	
Caps Lo	*		A		s	ľ	D	F		G		н		J	P	(	l		4	5	Ä		-					4	5	6 	+
() sivit		>		Y		×	ľ	2	V		в		N		μ					1		1	swn (Ci	ean on/uff)		1		1 Ende	2 ↓	3 Did J	
50g		E		At														AL	34	v	n.		•	Sing	+	4	-	0 Eintg		1 Def	Ent

Models may vary from the image shown

The reliable and durable AK-C8100 hygienic keyboard with its full layout is particularly suitable for frequent typists in hygiene-critical environments. The robust silicone cover with abrasion-resistant lettering prevents the ingress of water and other liquids and can be thoroughly wiped and disinfected in no time at all. Whether in a medical or industrial environment: the light, low-noise keystroke and precise key guidance mean that even large amounts of data can be entered efficiently and comfortably.

## FUNCTION AND PERFORMANCE

- → Full-layout keyboard with waterproof silicone cover
- → Approved for clinical wipe disinfection according to VAH list (German Association of Applied Hygiene)
- → Robust silicone cover with abrasion-resistant lettering
- → Maximum writing comfort thanks to scissor technology
- ightarrow Light, quiet keystroke
- → Clean function: keys are switched off during the cleaning process

## TECHNICAL DATA

Weight main product:	920 g
Weight of product without packaging:	930 g
Weight of product incl. packaging:	1,070 g
Weight of master carton incl. content:	11,600 g
Content of master carton (pieces):	10
Dimensions product without packaging:	449 mm x 142 mm x 26 mm
Dimensions product incl. packaging:	470 mm x 190 mm x 35 mm
Dimensions master carton:	360 mm x 215 mm x 497 mm
Cable length:	180 cm
Storage temperature:	-20 °C - 60 °C
Working temperature:	0 °C - 50 °C
Product approvals:	<ul> <li>CE</li> <li>FCC</li> <li>EU RoHS</li> <li>EN60601-1-2-2015 (IEC 4th edition)</li> </ul>
System Requirements- Hardware:	USB-A
Operating system:	All operating systems that support USB keyboard interface
Scope of delivery:	<ul><li>Keyboard</li><li>Manual</li></ul>
Reliability:	MTBF 90: > 10 Mio.
Switching characteristics:	tactile
Max. current consumption (mA) of keyboard:	45 mA
Actuating force (cN):	60 cN
Pre-Travel:	3 mm
Key labeling:	Silk screen printing on silicon membrane
Number of keys:	105
Special key functions:	<ul><li>FN Key</li><li>CleanFunction</li></ul>

 <sup>1 / 4 ©</sup> Cherry Digital Health GmbH • Rosental 7, c/o Mindspace, D-80331 Munich Phone: +49 9643 2061100 • www.cherry.de
 Postal Address: Cherrystr. 2, 91275 Auerbach i.d.OPf., Germany



Status LEDs:	in housing
Key technology:	Scissor
Keycap material:	ABS
Protection class:	<ul><li>Standard</li><li>IP 68</li></ul>
Warranty:	2 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.



SKU / EAN / UPC	Protection class	Color	Layout
AK-C8100F-UVS-B/GE EAN 7061111071238 UPC	IP 68	black	DE (Germany)
AK-C8100F-UVS-B/UK EAN 7061113258576 UPC	IP 68	black	GB (United Kingdom)
AK-C8100F-UVS-B/US EAN 7061115390212 UPC	IP 68	black	US (USA)
AK-C8100F-UVS-W/FR EAN 7061113480397 UPC	IP 68	white	FR (France)
AK-C8100F-UVS-W/GE EAN 7061118344687 UPC	IP 68	white	DE (Germany)
AK-C8100F-UVS-W/NOR EAN 7061117144271 UPC	IP 68	white	NOR (Nordic)
AK-C8100F-UVS-W/UK EAN 7061114569732 UPC	IP 68	white	GB (United Kingdom)
AK-C8100F-UVS-W/US EAN 7061115466023 UPC	IP 68	white	US (USA)
AK-C8100F-U1-B/GE EAN 7061111185331 UPC	Standard	black	DE (Germany)
AK-C8100F-U1-B/US EAN 7061112253893 UPC	Standard	black	US (USA)
AK-C8100F-U1-W/FR EAN 7061118042392 UPC	Standard	white	FR (France)
AK-C8100F-U1-W/GE EAN 7061114283874 UPC	Standard	white	DE (Germany)
AK-C8100F-U1-W/NOR EAN 7061117440229 UPC	Standard	white	NOR (Nordic)



SKU / EAN / UPC	Protection class	Color	Layout
AK-C8100F-U1-W/UK EAN 4025112098536 UPC	Standard	white	GB (United Kingdom)
AK-C8100F-U1-W/US EAN 7061119282612 UPC	Standard	white	US (USA)

Please contact your local CHERRY service and support teams or your CHERRY sales partners for versions available in your country.