AK-C7000

Compact Hygiene Keyboard with Numpad





- → CleanFunction enables deactivation of the keys before cleaning ("FN"+"Clean on/off")
- → Wipe disinfection in accordance with guidelines of the VAH-list
- → Exchangeable membrane system silicon key membrane can be exchanged
- → Machine reprocessing of the membrane at 93° and 134°C (in addition to wipe disinfection)
- → Flat key profile & smooth key actuation for perfect writing comfort

Models may vary from the image shown

Being completely sanitizable by wiping the AK-C7000 offers safe surface disinfection with utmost typing comfort. Due to its cleaning and disinfection capacities it is especially made for the use in hospitals, at practitioners and microbiological laboratories but also anywhere else when it comes to purity and hygiene at the workplace.

The silicon membrane protects keyboard and keyfield against dirt and fluids. The AK-C7000 convinces with smooth key actuation and precise key quidance.

Moreover it is highly recommendable for heavy duty type writing applications in hygiene critical areas.

FUNCTION AND PERFORMANCE

- \rightarrow Seamless closed surface
- → Fully sealed silicon membrane for Protection Class IP68
- → Silicon membrane with flat key profile and completely closed surface offers 360° safeguard against dirt and splash water
- \rightarrow Flat keys for thorough routine disinfection
- Proper wipe disinfection of the key field and keyboard reduces germ load

TECHNICAL DATA

Color:	white
Weight main product:	730 g
Weight of product without packaging:	800 g
Weight of product incl. packaging:	880 g
Weight of master carton incl. content:	17,500 g
Content of master carton (pieces):	20
Dimensions product without packaging:	374 mm x 139 mm x 25 mm
Dimensions product incl. packaging:	395 mm x 195 mm x 30 mm
Dimensions master	410 mm x 340 mm x 420
carton:	mm
Cable length:	180 cm
Storage temperature:	-20 °C - 60 °C
Working temperature:	0 °C - 50 °C
Product approvals:	 CE EU RoHS FCC EN60601-1-2-2015 (IEC 4th edition)
System Requirements- Hardware:	USB-A
Operating system:	All operating systems that support USB keyboard interface

Manual



Reliability: MTBF 90: > 10 Mio. Switching tactile characteristics: Max. current 25 mA consumption (mA) of keyboard: Actuating force (cN): 60 cN Total Key Travel: 3 mm Key labeling: Silk screen printing on silicon membrane Number of keys: 104 Special key functions: • FN Key CleanFunction Status LEDs: in housing Key technology: Scissor Keycap material: ABS

Reprocessing: • Recommended for Wipe Disinfection

 Approved for wipe disinfection according to CDC Guideline for Disinfection and Sterilization in Healthcare Facilities with EPA-registered disinfecting products
 Chemical-Thermal

 Chemical-Thermal Disinfection with IP68 Sealing Caps Mounted

Water Tight (IP68)

EAN: 7061111015959

Protection class: IP 68

Warranty: 2 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.