





CB₃ 47.2 x 39.4 x 29.1 " / 161 gal





Art.-Nr.: 83281510

Technical Data*1			
External Dimensions	47.2 x 39.4 x 29.1 " (1200 x 1000 x 740 mm)	Internal Dimensions	44.5 x 36.4 x 23.4" (1130 x 925 x 595 mm)
Weight(lbs)	80.5 lbs	Volume (I)	161.1 gal
Material* ²	PE		
Load capacity (lbs)	Stacking Load 11050 lbs	Holding Capacity 1,550 lbs	Dynamic Load 2650 lbs

Characteristics

Color: green

Manufactured in one piece Runners: 3, unwelded

Stackable

Temperature stability: -22°F to +104°F, briefly up to +194°F Resistant to most chemicals and cleaning agents

Food-safe. HACCP compliant

Container is based on DIN EN 13626 and DIN EN ISO 12048

Options

Transponder (RFID) Lid Drain port

Loading quantities (Pcs / Approximate amount)

Container

Container 20': 40 Container 40': -

Container 40' High Cube: 106

Conventional trailer 45' high cube container: -

Truck

MEGA-Trailer: 130

Jumbo: 140-150

Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.









- All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- Stacking Load: With a maximum stacking height of 6 boxes (5 on 1 stacking) and evenly distributed load at approx. 68 ° F. Dynamic Load: on a forklift with an evenly distributed load at a room temperature of approx. 68 ° F.